



BORE CONTROL

- 1) Bore entry is measured at 5 mm from the top.
- 2) Diameter at 20 mm is to be not greater than 19.5 mm.
- 3) The bore diameter for 20 mm must not be smaller than the bore at entry
- 4) The minimum through bore diameter is 16.8 mm.

THIS DRAWING IS THE PROPERTY OF

AMCOR GLASS
AUSTRALASIA
AND IS COPYRIGHT

NUMBER	AG 007 C01
NAME	750ml SPARKLING
CAPACITY	757ml ±7
FILL POINT	82.6mm
BRIMFULL	theor. 787ml
WEIGHT	680g
INTERNAL PRESSURE	Max 5 G.V.
FINISH NAME	CROWN CORK
FINISH NUMBER	C01
INITIAL ISSUE	22/04/02
REV C	Internal Pressure added.
REV B	Knurling and Stippling
REV A	Knurling and Stippling. Crescent Knurling.
DRAFT	Bearing Surface diameter added.
REV.	20/03/02
DATE	12/02/02

THIS DRAWING IS THE PROPERTY OF

AMCOR GLASS
AUSTRALASIA
AND IS COPYRIGHT

FINISH NAME	CROWN CORK MOUTH
FINISH NUMBER	C01
INITIAL ISSUE	22/04/02
DRAFT	12/02/02
REV.	DATE
DETAILS	

